DECT Phone System W710P(W710D+W610D)

Fanvil W710P is a DECT IP system designed for small and medium-sized businesses. Including the Base W710D and the handset W610D, it offers excellent mobility and flexibility, while eliminating the need for additional wiring costs. The system supports the registration of up to 10 Fanvil W610D DECT handsets and provides robust processing capacity for up to 20 SIP accounts and 10 simultaneous calls. Additionally, it supports LAN communication, allowing users to conduct internal calls without the need to register a SIP account. Fanvil IP DECT offers reliable wireless communication with high-quality voice service, perfect for dense user environments and short-range communication.



Sidekey

DSS

Dsskey

HD

HD Voice

UI

Smooth UI Interaction

Key Features

- Up to 10 simultaneous calls
- Up to 10 Handsets
- Up to 20 SIP accounts
- Up to 10 internal extensions
- Wireless signal coverage extends up to 50m indoors and 300m outdoors
- 2" 240 x 320 color screen with smooth user interface
- Support 16 virtual DSS Keys and 1 physical side key
- Local phone book: 1000 local contact for each terminal
- Support XML/LDAP Remote phone book
- Up to 8 hours' talk time and up to 160 hours standby time
- Support Intelligent Noise Reduction and Acoustic Shield

Specifications

Generic

• 10 simultaneous calls
• Wireless signal coverage: up to 50 meters indoors and 300 meters outdoors
• 10 terminals
• 20 SIP accounts
• 10 internal extensions
• 10 SIP Servers
• 2.0-inch 240*320 color high-definition LCD display
• Support 16 virtual DSS Keys and 1 physical side key
• HD Voice
• Incoming vibration alarm
• Auto-Answering/Speed Dial /Call waiting/ 6-way Conference
• Supports multiple languages:
English/Japanese/Korean/French/German/Dutch/Spanish/Italian/Polish /Portuguese/Greek/Turkish/Russian/Chinese/Tra-Chinese

Terminal Management

• Add/Delete/Import/Export
• Check terminal information
• Configure terminal: Reset, upgrade, DND
• Configuration management: 10 terminal configuration files
• Trouble removal: Capture package, syslog
• Local phone book: 1000 local contact for each terminal
• XML/LDAP phone book
• 20000 call logs
• Call log statistics: All, Incoming, Outgoing, Missed, Forwards

DECT

• Frequency band
1880~1900 MHz (European/South Africa):10 Channels，default item.
1920~1930 MHz (America/Canada):5 Channels
1893~1906 MHz (Japan):5 Channels
1880~1895 MHz (Taiwan,China):8 Channels
1910~1920 MHz (Brazil):5 Channels
1786~1792 MHz (South Korea):3 Channels
1910~1930 MHz (Latin America):10 Channels
1909~1929 MHz (Argentina):10 Channels

Network

• DECT protocol
• 10/100 Mbps Ethernet (Bridge connection)
• IP mode: IPv4/IPv6/IPv4&IPv6
• Static IP / DHCP
• 802.1x Network access permission authentication
• VPN: L2TP / OpenVPN
• VLAN
• LLDP
• CDP

Audio

• Narrowband Codec: G.711a/u, G.729, G.729A, G.729B, G.729AB
• Wideband Codec: G.722, Opus

Protocols

• DECT
• UDP/TCP/TLS
• RTP/SRTP
• STUN
• DHCP
• IPv6
• LLDP
• 802.1x
• L2TP
• openVPN
• SNTP
• FTP/TFTP/HTTP/HTTPS
• TR-069

Deployment & Maintenance

• Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP
PnP/TR-069
• Web management interface
• Web-based Packet-dump
• Configuration export/import
• Firmware upgrade
• Syslog

Specification

• W610D Drop Height: 1.8m
• Shell Material: Plastic Shell
•W710D DC Input: 5V/1A; W610D DC Input: 5V/2A
• W710D RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
• W710D Power: DC5V/1A or PoE
• W710D Power Consumption (POE): 1.17W-1.39W
• W710D Power Consumption (Power Adapter): 0.803W - 0.94W
• W710D Installation: Wall-mounted
• Working Temperature: -10°C ~ +45°C
• Storage Temperature: -20°C~ +60°C
• Working Humidity: 5% to 95%
• W710D Device Dimensions： 140*100*26mm
W610D Device Dimensions： 156*53*17. 7 mm
• Certifications: CE- EMC/CE-LVD/CE-RF/FCC SDOC/FCC ID/part68/ERP/DOE/CEC/SRRC/ROHS/WEEE/REACH

Package

• W610D Handset x1
• W710D Base Station x1
• Charging Base x1
• Belt Clip x1
• Rechargeable Battery x1 1900mAh
• Product Weight(with packing): 889g
• Qty/CTN: 10pcs
• N.W/CTN: 8.9kg
• G.W/CTN: 9.8kg
• Gift Box Dimension: 279*218*74mm
• Outer CTN Dimensions:456*395*299mm

About Fanvil

Fanvil Technology Co., Ltd. (Fanvil) is a leading global provider of A&V-IoT (Audio& Video- IoT) devices with three R&D centers in Beijing, Shenzhen, and Suzhou, China, and three factories in Huizhou and Shangrao, China, and Vietnam. Fanvil has focused on unified communication technology innovation for more than 20 years and provides SIP phones and SIP security industrial products in the global market, powering different businesses in the community, transportation, education, healthcare, enterprises, etc.

About LINKVIL

As the sub-brand of Fanvil, LINKVIL will focus on the research and development of A&V-IoT wireless communication products. Based on Audio & Video -IoT, LINKVIL helps to achieve the full connection of wireless communication systems. LINKVIL builds a wireless communication Eco-system for multi-scenarios to help accelerate digital transformation.

Copyright

Copyright © 2022 Fanvil Technology Co., Ltd.
All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Fanvil Technology Co., Ltd.

More Information

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.

For more information, please visit: www.fanvil.com

Fanvil Technology Co., Ltd.
Web：www.fanvil.com
Add:10/F Block A, Dualshine Global Science Innovation Center, Honglang North 2nd Road, Bao'an District, Shenzhen, China
Copyright © 2022 Fanvil Technology Co., Ltd.